

Magnetics for Telecommunications & Data Network Circuits

Common Mode Chokes

- For the rejection of RFI and EMI on unshielded twisted pair (UTP) lines
- 1000 VDC isolation
- Custom designs in a wide variety of packages



ELECTRICAL CHARACTERISTICS @ 25° C

BH PART NUMBER	TURNS RATIO	REFERENCE INDUCTANCE @ 100 KHz	CI MAX. ANY WINDING	DCR MAX	SCHEMATIC	PACKAGE STYLE	DIM "A"	DIM "B"
L00-1164	1:1	33 H	20pF	0.05	4	4		
500-1165	1:1:1:1	27 H	30pF	0.05	1	1	0.450	0.350
500-1179	1:1:1:1	53 H	30pF	0.1	1	1	0.590	0.500
500-1266	1:1	15mH	260pF	2.0	4	1	0.580	0.500
500-1267	1:1	125 H	150pF	0.5	4	1	0.580	0.500
500-1291	1:1	53 H	30pF	0.1	4	1	0.590	0.550
500-1299	1:1	750 H	15pF	0.3	3	2		
500-1433	1:1	750 H	15pF	0.3	3	2		
500-1517	1:1:1:1	50 H	20pF	0.15	1	1	0.420	0.350
500-1532	1:1:1:1	12 H	10pF	0.1	1	1	0.450	0.360
500-1841	1:1:1:1	8 H	10pF	0.20	1	3		
500-1910	1:1	85 H	10pF	0.08	4	4		
500-2063	1:1	64 H	30pF	0.2	2	5		
501-0752	1:1	12mH	350pF	14.0	2	6		

Note: Part numbers beginning with "L" are RoHS compliant.

